

Structured Media™ Center Retrofit



Improve RF transparency by adding a plastic cover or door to a metal enclosure

Easily transform your existing Leviton metal enclosure to support stronger wireless signals by adding a plastic Vented Cover or plastic Vented Hinged Door and Trim Ring.

Learn more at [Leviton.com/WirelessSMC](https://www.leviton.com/WirelessSMC)

Watch step-by-step videos at [Leviton.com/CH/Videos](https://www.leviton.com/CH/Videos)

- Plastic covers and doors improve will improve wireless signals transmitted from within the metal enclosure
- Adding a Vented Hinged Door creates Tri-Plane Heat Dissipation, which improves airflow and cooling for active equipment by as much as 40% over a vented metal door.
- The Vented Hinged Door and Trim Ring add depth, increasing capacity inside the enclosure

Trim Ring 49605-xxT | Vented Hinged Door 49605-xxS | xx = Size 14", 28", 42"

STEP

1



Loosen top two screws.
Remove bottom two screws
and existing metal door.

(For Vented Cover installation,
skip to Step 3.)

STEP

2



Assemble Trim Ring.

STEP

3



Hang Trim Ring or Vented
Cover and screw in place

(Cover installation is complete).

STEP

4



Snap Vented Hinged Door
onto hinge.