

Smart Sensors



Lighting Controls Done Right

Smart, simple sensing and switching or dimming control for virtually any application

Offering customers a complete code-compliant, easy-to-install, and easy-to-configure solution

App configurable with options for out-of-the-box operation

Select the sensing solution that best fits your needs—choose from simple standalone **Smart Wallbox Sensors** or for more advanced lighting control strategies, use **Smart Ceiling Mount Sensors**. For outdoor applications, use **Smart Fixture Mount Sensors**.







Smart Sensors

From standalone sensors to self-contained advanced lighting controls, Leviton has a smart solution for virtually any application. The Smart Sensor line is engineered to be easy to design, install, and configure for code compliance. Smart Wallbox Sensors, Smart Ceiling Mount Sensors, and Smart Fixture Mount Sensors are fully configurable with the Smart Sensor App.

For Distributors

- Stock less models to meet more project requirements
- Offer differentiating features for a competitive advantage
- Take advantage of competitive pricing

For Contractors

- Complete more projects faster for more profits—installation is quick and easy with less components for hardware, labor, and time savings
- Reduce callbacks with professional commercial-grade quality solutions
- Meet more project opportunities

For Building Owners and Facility Managers

- Implement simple to use code compliant solutions for increased energy savings
- Enable as little or as many capabilities as needed with scalable solutions
- Modify the lighting control system with the app to meet changing occupant needs and code changes

For Specifiers

- Specify lighting control solutions with confidence
- Comply with national and local energy codes with solutions that are easy to design, install, and commission
- Make client handoffs easier with easy-to-use customer interfaces



Smart Wallbox Sensors

Smart Wallbox Sensors combine occupancy/vacancy sensing with ON/OFF switching, 0-10V dimming, or 1000W dimming to provide a simple commercial grade solution for easy energy savings, local control, and code compliance. Smart Wallbox Sensors offer easy programming and configuration with the Smart Sensor App, an out-of-the-box default mode for auto-ON/auto-OFF operation with a 10-minute timeout, and convenient pushbutton programming for common room settings. Ideal for commercial spaces up to 1,100 SF including offices, meeting rooms, and lobbies.

Can be used to comply with IECC, ASHRAE 90.1, and Title 24, Part 6

Ladderless Commissioning with the Smart Sensor App

Select operating mode

Configure sensor settings (i.e. sensitivity, timeouts)

Enable partial-ON and partial-OFF

Configure daylighting settings

Program scheduling

Create multi-room templates

Select nightlight color

Combines occupancy/vacancy sensing and ON/OFF switching

Combines occupancy/vacancy sensing and 0-10V or 1000W dimming

Occupancy/vacancy sensing

PIR only and multi-tech (PIR & microphonics) models

ON/OFF switching

0-10V dimming and 1000W dimming

Partial-ON and partial-OFF

Ambient light hold-OFF

Add a power pack and controlled receptacles for plug load control

Antimicrobial models available

Choose from out-of-the-box default mode, pushbutton programming, or app configuration

Push-to-pair programming for multi-way control for up to 5 devices



Smart Ceiling Mount Sensors

Smart Ceiling Mount Sensors (CMS) deliver an all-in-one code compliant solution. The line simplifies advanced lighting controls by integrating several control strategies into a self-contained, cost-effective, easy-to-install, and easy-to-configure device. Ideal for education, commercial spaces, healthcare, hospitality, and retail applications.

System fine-tuning and adjustments from the palm of your hand

Manual control with wireless switching, wireless dimming, or 1-, 2-, and 4-button keypad options

Can be used to comply with IECC, ASHRAE 90.1, and Title 24, Part 6

Integrated occupancy/vacancy sensor, photocell, and power pack in a self-contained device

Ladderless Commissioning with the Smart Sensor App

Select sensing technology

Select operating mode

Configure sensor settings

Enable partial-ON and partial-OFF

Configure daylighting settings

Network devices to expand field-of-view (FOV) coverage up to 10,000 SF

Control up to 10 zones independently

Program scheduling

Create multi-room templates

Wireless multi-way control

Standalone, networkable advanced lighting control

Occupancy/vacancy sensing

0-10V dimming, partial-ON, and partial-OFF

ON/OFF switching

Daylight harvesting

Ambient light hold-OFF

Automatic closed or open loop daylighting

Plug load control

Demand response

Out-of-the-box default mode

UL924 Listed for emergency lighting

Single and dual relay models include 2 interchangeable lenses and aisleway masks



Smart Fixture Mount Sensors

Smart Fixture Mount Sensors are IP66 rated and designed for use with switching, 0-10V LED dimming drivers, and fluorescent ballasts. The sensors use PIR detection technology and advanced optics to provide an exceptional field-of-view (FOV) for mounting heights from 8 to 40 feet. Configuration is made using the Smart Sensor App. Ideal for warehouses, parking lots and garages, outdoor sports facilities, and building facades.

Ladderless Commissioning with the Smart Sensor App

- Select operating mode
- Configure sensor settings (i.e. sensitivity, timeouts)
- Enable partial-ON and partial-OFF
- Configure daylighting settings
- Grouping
- Program scheduling (universal models only)
- Create multi-room templates

Can be used to comply with IECC, ASHRAE 90.1, and Title 24, Part 6

Internal fixture mount model

End/external fixture mount model

Occupancy/vacancy sensing

IP66 Rated

ON/OFF switching

0-10V dimming

Partial-ON and partial-OFF

Multiple daylighting modes: ambient light hold-OFF (switching), daylight harvesting (dimming), and daylight transition lighting (reverse daylight harvesting)

Largest field-of-view for 8' to 40' mounting heights

Universal voltage models

Out-of-the-box default mode

Includes low bay and high bay lenses and aisleway masks

Smart Wallbox Sensors Comparison

Smart Wallbox Sensors



ODS15-IDx
ODS15-GDx
ODS15-I1x

ODD10-IDx

ODD24-IDW

ODP10-I1x

Technology	PIR			
Mounting	Wall			
Coverage (SF)	1,100			
Pattern	180°			
Mounting Height	40' to 48"			
Configuration	Out-of-the-box default mode, pushbutton programming, app configurable with the Smart Sensor App			
Timeouts	30 sec, 5 min, 10 min, 20 min, 30 min, and 60 min			
Voltage	120-277VAC, 50/60Hz (ODS15-IDx, ODS15-GDx) 120VAC, 60Hz (ODS15-I1x)	120-277VAC	24V	120VAC
Occupancy or Vacancy	Occupancy and vacancy			
Dimming	Switching only	0-10V dimming	24V dimming	1000W dimming
Daylighting	Ambient light hold-OFF			
Other	Connect up to 5 devices for multi-way control; create multi-room templates for fast room replication			
Listing	UL, cUL, FCC, IECC, IC			
Code Compliant	Can be used to comply with IECC, ASHRAE 90.1, and 2022 Title 24, Part 6 occupancy/vacancy, dimming, daylight harvesting, and plug load control requirements			

Smart Wallbox Sensors Comparison

Smart Wallbox Sensors



ODSMT-MDx

ODDMT-MDx

ODDMT-MLx

ODP10-M1x

Technology	Multi-Technology (PIR & microphonics)			
Mounting	Wall			
Coverage (SF)	1,100			
Pattern	180°			
Mounting Height	30' to 40"			
Configuration	Out-of-the-box default mode, pushbutton programming, app configurable with the Smart Sensor App			
Timeouts	30 sec, 5 min, 10 min, 20 min, 30 min, and 60 min			
Voltage	120-277VAC		24V	120VAC
Occupancy or Vacancy	Occupancy and vacancy			
Dimming	Switching only	0-10V dimming	24V dimming	1000W dimming
Daylighting	Ambient light hold-OFF			
Other	Connect up to 5 devices for multi-way control; create multi-room templates for fast room replication			
Listing	UL, cUL, FCC, IECC, IC			
Code Compliant	Can be used to comply with IECC, ASHRAE 90.1, and 2022 Title 24, Part 6 occupancy/vacancy, dimming, daylight harvesting, and plug load control requirements			

Smart Ceiling Mount Sensors Comparison

Smart Ceiling Mount Sensors (CMS)



	ACY15-DIW	AC705-DMW ACY20-DMW	ACS15-DIW	ACS05-DMW ACS10-DMW ACS20-DMW	AC205-DMW AC220-DMW
Technology	PIR	Multi-Technology (PIR & U/S)	PIR	Multi-Technology (PIR & U/S)	Multi-Technology (PIR & U/S)
Mounting	Ceiling Mount				
Coverage (SF)	450-1,500	500 2,000	450-1,500	500 1,000 2,000	500 2,000
Pattern	180° (AC705 and ACS05), 360° (all others)				
Mounting Height	6' to 20'				
Configuration	Out-of-the-box default mode, pushbutton programming, app configurable with the Smart Sensor App				
Time Delay	30 sec, 5 min, 10 min, 20 min, 30 min, and 60 min				
Voltage	120-277VAC				
Number of Zones	2	1 (AC705-DMW) 2 (ACY20-DMW)	1	1	2
Occupancy or Vacancy	Occupancy and vacancy				
Dimming	0-10V dimming		Switching only		
Partial-ON/ Partial-OFF	Yes		No		
Daylighting	Daylight harvesting		Ambient light hold-OFF		
Scheduling	Yes		Yes (when paired with AC705, ACY15, or ACY20)		
Manual Control	PLVSW 1-, 2-, and 4-Button Low Voltage Keypads, Wireless Companion Switch, or Wireless Companion Dimmer		PLVSW 1- and 2-Button Low Voltage Keypads or Wireless Companion Switch		
Other	Combines occupancy/vacancy sensor, photocell, and power pack; includes 2 interchangeable lenses and aisleway masks; independent zone control for up to 10 zones; wirelessly network up to 5 Smart Ceiling Mount Sensors to expand FOV up to 10,000 SF; multi-way control; create multi-room templates for fast room replication; UL924 Listed for emergency lighting				
Listing	UL773A (Occupancy Standard), UL924 (Emergency Equipment), cUL Listed, NOM Certified, RoHS Compliant, NY LLC48 Compliant				
Code Compliant	Can be used to comply with IECC, ASHRAE 90.1, and 2022 Title 24, Part 6 occupancy/vacancy sensing, 0-10V dimming, partial-ON, partial-OFF, daylight harvesting, demand response, and plug load control requirements		Can be used to comply with IECC, ASHRAE 90.1, and 2022 Title 24, Part 6 occupancy/vacancy sensing, demand response, and plug load control requirements		

Smart Fixture Mount Sensors Comparison

Smart Fixture Mount Sensors (FMS)



ZLD1Z-I0W

ZLDUZ-I0W

OFD1Z

OFDUZ

Technology	PIR			
Mounting	Internal fixture mount		End/external fixture mount	
Coverage (SF)	Up to 8,250			
Pattern	360°			
Mounting Height	8' to 40'			
Configuration	Out-of-the-box default mode and app configurable with the Smart Sensor App			
Timeouts	30 sec, 5 min, 10 min, 20 min, 30 min, and 60 min			
Voltage	120-277VAC	120-480VAC	120-277VAC	120-480VAC
Occupancy or Vacancy	Occupancy			
Dimming	0-10V dimming			
Daylighting	Multiple daylighting modes: ambient light hold-OFF (switching), daylight harvesting (dimming), and daylight transition lighting (reverse daylight harvesting)			
Scheduling	No	Yes	No	Yes
Other	IP66 rated, includes 2 interchangeable lenses and aisleway masks; create multi-room templates for fast room replication			
Listing	UL, cUL, FCC, IECC, IC			
Code Compliant	Can be used to comply with IECC, ASHRAE 90.1, and 2022 Title 24, Part 6 occupancy sensing, dimming, and daylight harvesting requirements			



Leviton Manufacturing Co., Inc. Global Headquarters

201 North Service Road, Melville, NY 11747-3138 **tel** 800-323-8920 **tech line** (8:00AM-10:00PM ET Mon-Fri, 9:00AM-7:00PM ET Sat, 9:00AM-5:00PM ET Sun) 800-824-3005

Leviton Manufacturing Co., Inc. Lighting & Controls

10385 SW Avery Street, Tualatin, OR 97062 **tel** 800-736-6682 **tech line** (6:00AM-4:00PM PT Mon-Fri) 800-959-6004

Visit our website at: www.leviton.com/smartsensors

©2024 Leviton Manufacturing Co. Inc. All rights reserved. Subject to change without notice.

LES-G-10740B/L24-cds
REV DEC 2024