


MLC 128R



BACK VIEW

The MLC 128R lighting control console from Leviton-NSI is extraordinary, delivering powerful design tools to help you develop everything from simple shows to exciting, elaborate events.

With the MLC 128R's pre-established library of lighting fixtures, you can simply and quickly control up to 128 of the latest and most powerful intelligent devices. Show design is a snap with the ingeniously organized front panel that addresses your need for programming flexibility. And the unit provides as many as 1,024 user-programmable scenes to handle any lighting challenge.

Take creative command of your intelligent lighting presentation with the fully programmable, rack mount MLC 128R control system from Leviton.

DIMENSIONAL DATA - IN. [CM] LBS. [KG]	
Width	18.90 [48.2]
Height	6.95 [17.7]
Depth	2.25 [8.7]
Weight	17.90 [8.1]



SPECIFICATIONS

- Controls up to 128 individual intelligent devices
- 512 DMX control channels
- 128 Micro-Plex control channels
- Up to 1,024 scenes. A scene is a static stage look, which is recorded into memory for later recall
- 256 patterns, each with up to 13,913 small steps, or 665 large steps. A pattern is a series of scenes linked together, played back in a timed sequence or repetition
- Stores 256 shows containing up to 24 patterns.
 A show is a series of linked patterns, which can be used as building blocks to create elaborate stage effects
- Up to 64 group assignments. A group is a number of devices, all controlled in unison
- Two line, 40 character backlit, adjustable contrast LCD display
- Fade times from .1 seconds to 59 minutes, 59.9 seconds

PORTS

- DMX512 (3 pin XLR female)
- Micro-Plex (3 pin XLR male and female)
- MIDI in/out/through (5 pin DIN)
- RS232 (g pin D-Sub/DBg male)
- Audio In (RCA type female)

CAT. NO.	DESCRIPTION
NMLC1-28R	Moving Light Controller - up to 128 Individual DMX512 luminaires, 1096 Programmable
	Scenes, 256 Patterns and 256 Shows, MIDI in/out/thru, Audio Sync, DMX512 Input and
	Output Ports, 120V

FEATURES

- Device focus edit feature simplifies setup of pre-programmed shows for playback in different venues
- A large library of popular fixture definitions pre-loaded. Additional definitions may be downloaded from the device definition disk included, or from our web site: www.nsicorp.com
- Lighting device definition creation and editing capabilities, as well as alphanumeric naming for identification of all devices, traits and indexed positions
- Group function allows control of similar traits in multiple devices
- Four encoder wheels for precise selection and easy modification of device trait information
- Joystick provides real time pan and tilt control
- RS-232 port enables mouse, trackball and PC interface
- Front and rear panel access to RS-232 port allows easy connection to laptop or PC for show storage and device definition downloads
- MIDI activation of any of the scenes, patterns or shows programmed in the MLC 128R
- Audio synchronization for triggering from a remote line-level audio source, such as a compact disc player or audio mixing console
- ASCII offline editor enables use of a simple word processor to create shows, device definitions and programs
- Device traits are displayed as words, rather than numeric values, for ease of operation
- Blind and go functions allow modifications to devices and groups to be made without affecting current stage look until the user chooses to activate the changes

LEVITON SPECIFICATION SUBMITTAL	
JOB NAME:	CATALOG NUMBERS:
JOB NUMBER:	

Leviton Manufacturing Co., Inc. Lighting Management Systems

20497 SW Teton Avenue, Portland, OR 97062

Telephone: 1-800-736-6682 • FAX: 503-404-5594 • Tech Line (6:00AM-4:00PM P.S.T. Monday-Friday): 1-800-959-6004

Leviton Manufacturing of Canada, Ltd.

165 Hymus Boulevard, Pointe Claire, Quebec HgR 1Eg • Telephone: 1-800-469-7890 • FAX: 1-800-563-1853

Leviton S. de R.L. de C.V.

Lago Tana 43, Mexico DF, Mexico CP 11290 • Tel. (+52) 55-5082-1040 • FAX: (+52) 5386-1797 • www.leviton.com.mx

Visit our Website at: www.leviton.com/lms