

Berk-Tek Indoor/Outdoor Riser Premises Distribution w/Armor-Tek™ (PDRK-I/O)

Berk-Tek's Riser rated Indoor/Outdoor Premises Distribution cables are designed specifically for LAN/WAN campus and building backbone cabling infrastructure. Armor-Tek Interlocking Armor is wound around the cable core. Suitable for Indoor/Outdoor installations, below the frost line.

DESCRIPTION

Berk-Tek's tight buffered indoor/outdoor riser interlock armored cables are designed for installation in riser and horizontal environments and interbuilding backbone structures.

This design incorporates tight buffered optical fibers within a dry water blocked core cable. Interlock armor and an outer jacket are added over the cable core. Suitable for operation across wide temperature variations typically addressed by outside plant cables. No Buffer Tube Fanout kits are required. Direct termination is enabled.

Construction

Each cable utilizes our DryGel water blocking system in the core cable. Cable design can accommodate from 2-144 tight buffered (900 µm) fibers. A glass reinforced (GRP) anti-buckling member is centrally located within cables having fiber counts from 24-144.

OFCR Rated. Available with aluminum steel interlock armor, covered by a riser rated jacket.

Outdoor Considerations

- For use in conduit, below the frost line.
- Sunlight resistant per UL 444 clause 7.22
- Loose Tube cables are recommended if interbuilding conduit systems lie above the frost line and are likely to fill with water.
- Tight Buffer fiber cables are not suitable for aerial-lashed installations.

Applications


Berk-Tek's tight buffered Interlocking Armor cable is intended for all high speed data applications including:

- ETHERNET: 10BASE – 40GBASE (10BASE, 100BASE, 1000BASE, 10GBASE, 40GBASE, 100GBASE, 400GBASE)
- Fibre Channel: 1G-FC – 128GFC (1, 2, 4, 8, 16, 32, 128 GFC)
- SONET: OC-1 – OC-768 (OC -1, 3, 12, 24, 48, 192, 768)
- SDH: STM-0 – STM-256 (STM-0, 1, 4, 16, 64, 256)
- OTN: OTU-1 – OTU4 (OTU1, 2, 2e, 2f, 3, 3e2, 4)
- CPRI: CPRI-1 – CPRI-9 (CPRI-1, 2, 3, 4, 5, 6, 7, 7a, 8, 9)
- PON (SMF only): RFoG, APON, BPON, EPON, GPON, WDM-PON, NG-PON

Features

- Flexible 900 µm tight buffered construction
- High tensile strength cost-saving design, easy to install and terminate
- Two to 144 count fiber construction riser rated indoor/outdoor designs ideal for backbone installations
- Single-mode, multimode, and hybrid designs available
- Also available in low smoke zero halogen design

Benefits



STANDARDS

International EN 50173; ISO/IEC 11801

National ANSI/ICEA S-104-696; ANSI/TIA-568.3-D; Telcordia GR-409

- Cost-saving design, easy to install and terminate
- Provides for greater pulling distances thus reducing installation time
- Assurance that cables will meet required specifications for communication networking applications
- Broad design selection allows for mix and match of fiber components to specific networking applications
- One cable design meeting all structured cabling network communications applications

Country of Origin: U.S.A.

CHARACTERISTICS

Construction characteristics

Type of cable	Tight Buffered (TB)
Jacket Material	Riser
Armour type	Aluminum Interlock

Usage characteristics

RoHS compliant	Yes
----------------	-----

TECHNICAL DATA - PHYSICAL						Install		Long Term		Install		Long Term	
Fibers	Part Number Prefix	Diameter		Weight		Min. Bend Radius				Max. Loading			
		in.	mm	lb./kft	kg/km	in.	cm	in.	cm	lbf.	N	lbf.	N
6	PDRK006-I/O(BLA)	0.624	15.8	120	179	9.4	23.8	6.2	15.8	150	667	45	200
12	PDRK012-I/O(BLA)	0.624	15.8	126	188	9.4	23.8	6.2	5.8	150	667	45	200
24	PDRK024-I/O(BLA)	0.690	17.5	166	248	10.4	26.3	6.9	17.5	150	667	45	200
36	PDRK12B036-I/O(BLA)	0.961	24.4	277	412	14.4	36.6	9.6	24.4	300	1335	90	400
48	PDRK12B048-I/O(BLA)	0.961	24.4	301	448	14.4	36.6	9.6	24.4	600	2670	180	800
72	PDRK12B072-I/O(BLA)	1.080	27.4	397	591	16.2	41.1	10.8	27.4	600	2670	180	800
96	PDRK12B096-I/O(BLA)	1.265	32.1	521	778	19.0	48.2	12.7	32.1	600	2670	180	800
144	PDRK12B144-I/O(BLA)	1.265	32.1	539	802	19.0	48.2	12.7	32.1	1000	4445	300	1335

TECHNICAL DATA										
Fiber Type	Part Number Suffix	Berk-Tek Fiber	Core Size	Wavelength (nm)	Maximum Attenuation (dB/km)	Effective Modal Bandwidth @ 850 nm (MHz·km)	Distance (meters)			
Multimode - Bend Insensitive							1 GbE	10 GbE	40 GbE	100 GbE
OM1	CB3510/25	GIGAlite	62.5 µm	850/1300	3.5/1.0	200	300	33	N/A	N/A
OM3	EB3010/25	GIGAlite-10	50 µm	850/1300	3.0/1.0	2000	1000	300	100	70
OM4	FB3010/F5	GIGAlite-10FB	50 µm	850/1300	3.0/1.0	4700	1040	550	150	100
OM4+	XB3010/X5	GIGAlite-10XB	50 µm	850/1300	3.0/1.0	4900	1210	600	300	150
WideBand Multimode - Bend Insensitive							1 GbE	10 GbE	40 GbE	100 GbE
OM5	WB3010/W5	GIGAlite-10WB	50 µm	850-953/1300	3.0/1.0	4700	1040	550	190	100
Single-Mode - Bend Insensitive - ITU-T G.652.D and G.657.A1 Compliant							1 GbE	10 GbE	40 GbE	100 GbE
OS2	AB0707	Standard for Tight Buffer	SMF	1310/1550	0.5/0.5	N/A	≥ 5000	≥ 10000	≥ 10000	≥ 10000

STANDARD SHEATH COLORS - TIGHT BUFFER - BLACK

Fiber Type	Core Size (µm)	ISO-TIA Standard	Effective Modal BW @ 850 nm	Overfilled Launch BW @ 850 nm	Attenuation @ 850 nm	Attenuation @ 1300 nm	Attenuation @ 1550 nm	Sheath Color
AB	8.3	OS2	NS	NS	NS	0.5 dB/km	0.5 dB/km	Black
CB	62.5	OM1	200 MHz·km	200 MHz·km	3.5 dB/km	1.0 dB/km	NS	Black
EB	50	OM3	2000 MHz·km	1500 MHz·km	3.0 dB/km	1.0 dB/km	NS	Black
FB	50	OM4	4700 MHz·km	3500 MHz·km	3.0 dB/km	1.0 dB/km	NS	Black
XB	50	OM4+	4900 MHz·km	3675 MHz·km	3.0 dB/km	1.0 dB/km	NS	Black
WB	50	OM5	4700 MHz·km	3500 MHz·km	3.0 dB/km	1.0 dB/km	NS	Black

NS = Not Specified

MANUFACTURING RELEASE

IMPORTANT NOTICE: This product specification is provided for informational purposes only in order to illustrate typical product constructions, applications and/or methods of installation. Because conditions of actual installation and use are unique and will vary, Berk-Tek makes no representation or warranty as to the reliability, accuracy or completeness of this data, even if Berk-Tek is aware of the product's intended use or purpose. Furthermore, this data does not constitute, nor should it be regarded or relied upon, as professional engineering advice. Installation of product should only be done by qualified personnel and in conformance with all safety, electrical and other applicable codes, standards, rules or regulations. Appropriate and correct product selection, installation and use, and compliance with all such codes, standards, rules and regulations, is a customer/end-user responsibility. Product specifications, standards, programs or services are subject to improvement or changes without notice. Berk-Tek accepts no liability for typographical errors, technical inaccuracies, omissions or misuse of the information contained herein. Changes will be periodically made to address any such issues.